

HPP 25 SP - ProLine Hand Pallet Truck Standard Features



- Capacity: 5,500 lb (2,500 kg)
- Fork length: 48" (1,220 mm)
- Fork outside width: 27" (685 mm)
- Steering wheels: 7.9" Ø x 2" wide (200 x 50 mm) polyurethane on cast alloy with dust caps to cover bearings. Rubber treads available at no additional cost.
- Fork rollers: 3.2" Ø x 3.6" wide (82 x 92 mm) single polyurethane. Tandem optional.
- Steering turning angle: 105 degrees to each side, 210 degrees total.
- Lowered height: 3.3" (85mm)
- Raised height: 7.9" (200 mm)
- High tech pump with hard chrome plated cylinder and galvanized housing.
- Low temperature hydraulic oil for reliable winter operation outdoors.
- Grease fittings at all pivot points.
- Low-effort pump action, up to 30% less effort at full load than most competitors, 10 strokes to maximum lift.
- Reinforced forks, apron and apron head for maximum strength and long life in demanding applications.
- Rounded fork tips for easy pallet entry, formed in one piece without welds for greater strength.
- Fork entry and exit rollers.
- Solid steel, adjustable push-bars.
- Powder-coated frame and handlebar resists scuffing.
- Ergonomic handlebar is coated with resilient plastic material to remain comfortable and rust-free.